



REFLECTIVE COATINGS

Aluminum pigments for Radiation Reflection Exterior & Interior

Edris Giunta, Milano Colori Coatings - Sales & Technical Service



Agenda

- ► Milano Colori / Eckart
- **▶** Product Range
- ► Application fields
- ► Aluminum Pigment Reflectivity
- **►** Exterior
- **▶** Interior
- **▶** Development









Who We Are

Over the years Milano Colori has established its role as a leader and reference point in the Italian and European market for the distribution of chemicals raw materials and special chemicals for industrial use.

- SUPPLIER OF MAIN ITALIAN PRODUCERS
- PARTNERSHIP WITH LEADING CHEMICAL MANUFACTURERS
- FOCUS ON INNOVATIVE PRODUCTS
- TECHNICAL AND COMMERCIAL CAPABILITIES
- EFFICIENT LOGISTICS MANAGEMENT





MILANO COLORI -Business Units





PERSONAL CARE



PLASTIC & RUBBER



HYGIENE & DETERGENCY



INDUSTRIAL CHEMICALS




FOOD & FEED




Our Business Model



ECKART Effect Pigments



ECKART Effect Pigments Product Range and Services














Energy Balance in Buildings






Radiation Indoor vs. Outdoor

Exterior

Solar radiationSpectrum UV / Visible / **NI**R

Desired functionality

 Reduction of heat inside the home through the reflection of heat towards the outside.




Interior

Thermal radiation

Objects such as radiators, walls, and humans emit **MI**R (20-100°C)

Desired functionality

- Reduction of energy consumption reflection of heat inwards.
- Thermal comfort.









STAPA® Aluminium Flakes as "Reflectors"

- Aluminium provide high reflective properties across all wavelength in comparison to TiO₂
- Flake shaped particles work like a mirror and best suitable




In Exterior Applications – Mode of Action


 Highly reflective (white) wall sunlight is reflected; high emissivity ε = 0,9 wall gets cool



 High absorptive (black) wall sunlight is absorbed; heat build-up; high emissivity ε = 0,9 cooling during night



 Low emissivity wall with "Aluminum Pigment" low heat emission ε = 0,3 -0,7 (depending on formulation) no cooling; no algae / mildew








Outdoor: Growth of Algae and Mildew

Exterior wall without insulation (old buildings)

- -> wall surface temperature higher than environment
- -> no microbial attack




Energy efficient wall; perfectly insulated

- -> wall surface temperature lower than environment
- -> water condensation
- -> microbial attack (algae / mildew formation) and subsequent degradation

Use of toxic biocides is common (short term efficiency).

→ Long Term: Low emissivity paint with "Aluminum Pigment"







In Exterior Applications

- Preventing water condensation on the façade stops the growth of microorganisms.
- Exterior wall coat containing low emission paint containing Aluminum Pigments
- Low-emission paints retain more heat in the plaster and release it over a longer period of time.
- In this way the façade remains warmer reducing the formation of condensation water
- No formation of algae and mildew

Fraunhofer Institute for Construction Physics

- Initial results confirm for low emissivity paint with significantly reduces water condensation on exterior walls.
- After 3 ½ years of exposure: no growth of algae and mildew while "normal" exterior walls displayed algae and mildew growth






Aluminum Pigment Characteristics → Application / Customers Choice

Non-leafing Pigments → SOLVENT BORNE & WATERBORNE (STABILIZED)



- Smooth effect
- No Mirror
- Good Adhesion
- Good Overcoating
- Good tinting properties

STAPA®
Metallic / Mobilux






STAPA® HYDROXAL E STAPA® HYDROLAN



Leafing Pigments → **SOLVENT BORNE**



- Highly Reflective (Mirror effect)
 - Light
 - Heat
- Barrier Protection
 - Moisture
 - Oxygen
- Fair Overcoating

STAPA® LEAFING






INTERIOR: ECKART Solution | IReflex

Standard white paint

Paint containing IReflex

- Off white / no metallic charakter
- fully encapsulated aluminum powder
- Tintable









Reflectivity of Radiation; Interior

Wall Thermal radiation **Paint Standard white paint** Absorption 95% Reflection 5% Thermal radiation Paint containing **iR**eflex Absorption 50% Reflection 50% Keflex







iReflex Independent Study: Results of ENERGY SAVING STUDY

Simulated room	Type of construction	Wall temperature inner side	Saving
two walls facing outside and ceiling	Old building	14,7 °C	22 %
	Building of the 1970	16,4 °C	19 %
	Passive House	19,6 °C	16 %
just a wall facing outside	Old building	14,7 °C	17 %
	Building of the 1970	16,4 °C	17 %







Independent Study



Bauhaus-Universität Weimar



Independent study conducted at BAUHAUS UNIVERSITY* in Weimar

*Faculty of Construction Physics.

- Inhouse application in air conditioned chamber
- "Feelix" wired with 7 km of electrical cables and sensors to mimic human body`s thermal comfort
- Comparative testing standard white wall paint vs. iReflex containg wall paint

Test conditions:

- Underfloor heating
- Outside temperature: -5 °C
- Initial room temperature: +21 °C
- Painting: based on Shinedecor IReflex 5000 White with a 50% reflection value
- Feelix heat flow density: q = 70.2 W/m² Comfort point of an average human body





INTERIOR: Shinedecor – Effect Pigment Concentrates



Properties:

- ready to use
- easy to use
- free of VOC, free of APEO, free of plasticizers
- high pigment loading
- excellent wetting properties
- excellent shear stability
- no sedimentation
- Suitable for automated dosing
- Shelf Life 12 months

Important things to know:

- Don't use high shear forces to incorporate our Shinedecors because this can destroy the metallic effect.
- We recommend to use at least 20% of Shinedecor in total formulation
- Depending on the required effect there can be used both, transparent wallpaints or colored wall paints (white Metallic).
- Shinedecor was originally developed for wallpaints, but can be used in every waterbased paint system (but this should be tested for compatibility before)





ECKART Effect Pigments

Dust-free, Low-VOC Pigment Preparation - VERSALAN





Discover the Revolution in Pigment Technology

Encapsulated pigments for waterborne coatings are our strength

- for decades!

Our newest pigment development – a dust-free, low-VOC preparation, made from pure aluminum with an inorganic coating:

- Environmentally Friendly: With a VOC content of less than 5%, it meets the latest regulatory requirements.
- Dust-Free: The preparation is dust-free and contains no additional binder system.
- Versatile: Suitable for water- and solvent-borne binder systems. It is easy to disperse and offers improved wetting properties.
- Excellent Coverage: Thanks to the latest STAPA® HYDROLAN® technology as base, it provides high gassing and chemical resistance.
- Regulatory Benefits: It is not classified as hazardous material, does not require separate storage and meets the requirements of the 4.1 burn test.









Contatti

Edris Giunta

Mail: giunta@milano-colori.com

Cell: 347 3140405

info@milano-colori.com

